

PRESS RELEASE

PRESS RELEASEOctober 4, 2017 || page 1 | 2

Parts2Clean: Inline measuring system

Detecting impurities on 3D components

Impurities adhering to the surface of components can cause problems in later stages of the production process – or even make the entire component useless. A new fluorescence scanner developed by the Fraunhofer IPM allows specialists to inspect metallic parts for residues of grease, machining chips and cleaning agents – for every single item in production cycle. The inline-measuring system will be presented at the Parts2Clean trade show from October 24 to 26, 2017

The smallest of details can have huge consequences. For instance, tiny particles of dirt clinging to the surface of components during the production process. The oil pan in vehicle engines is a typical example. If the process lubricant contains impurities that stick to the areas where the sealant will be applied, the seal will not be tight and the oil pan is likely to leak at this vulnerable point. Until now, it has not been technically possible to examine every single component for residual contaminants. The only solution was to test random samples, which is not only time-intensive but also fails to identify the exact spot on the component contaminated by foreign substances.

Spatially resolved inline measurement = 100% quality

In future, manufacturers won't need to worry about such questions of contamination. The answer lies in the inline fluorescence scanner developed by researchers at Fraunhofer IPM. "This scanner not only enables us to perform inline measurements on every single metallic component – during the production process and without requiring additional time – but also enables us to pinpoint the exact location of the dirt particles," explains Andreas Hofmann, Business Development Manager at Fraunhofer IPM. "The outstanding spatial resolution of this system enables us to identify even the slightest deposits or films of less than ten milligrams per square meter."

Fluorescence detectors for oil films, machining chips and other contamination

The system works as follows: While an oil pan travels from point A to B on the conveyor belt, a point-source UV laser scans a specific area of the component. If traces of grease, remains of organic cleaning fluids, or fibers are detected on the surface, they reflect light in the visible fluorescence spectrum as a sort of response to the laser's

Editor

Holger Kock | Communications and Media | Fraunhofer Institute for Physical Measurement Techniques IPM | Heidenhofstrasse 8 | 79110 Freiburg |
Phone +49 761 8857-129 | holger.kock@ipm.fraunhofer.de | www.ipm.fraunhofer.de/en

FRAUNHOFER INSTITUTE FOR PHYSICAL MEASUREMENT TECHNIQUES IPM


UV light. The sensitive detector that captures these light frequencies ignores all other wavelengths, and is thus able to interpret the fluorescence signals as signs of contamination. The metallic component itself does not reflect beams of fluorescent light. A scanner ensures that the laser focus passes over the surface at high speed, creating a point-by-point grid. The laser beam scans the object at a rate of approximately 200 times per second. As a result, the quality controller receives an image showing precisely where any dirt particles or oil films have been detected. The fluorescence scanner is even capable of detecting metallic chips that adhered to the test object in previous machining steps, even though they are not fluorescent. "The preprocessed components are cleaned using water or compressed air. Any remaining chips are contaminated with oil or other fluorescent substances," says Hofmann.

PRESS RELEASE

October 4, 2017 || page 2 | 2

Spatial resolution and processing speed adaptable to the production process

The researchers can adapt the system's spatial resolution and processing speed to the needs of the production process, for instance just-in-time manufacturing. And the fluorescence scanner is not restricted to applications involving metallic components – although further studies will be needed to adapt it to other materials. The researchers will present their inline measuring system at the Parts2Clean trade show in Stuttgart from October 24 to 26, 2017 (Hall 5, Booth C31).



The fluorescence scanner – an imaging, inline measuring system – inspects components for impurities during the manufacturing process and identifies the exact point of contamination.

Photo © Fraunhofer IPM | www.ipm.fraunhofer.de.

The **Fraunhofer-Gesellschaft** is the leading organization for applied research in Europe. Its research activities are conducted by 69 institutes and research units at locations throughout Germany. The Fraunhofer-Gesellschaft employs a staff of 24,500, who work with an annual research budget totaling 2.1 billion euros. Of this sum, 1.9 billion euros is generated through contract research. More than 70 percent of the Fraunhofer-Gesellschaft's contract research revenue is derived from contracts with industry and from publicly financed research projects. International collaborations with excellent research partners and innovative companies around the world ensure direct access to regions of the greatest importance to present and future scientific progress and economic development. .

Other contacts

Dr. Albrecht Brandenburg | Optical Surface Analytics | Phone +49 761 8857-306 | albrecht.brandenburg@ipm.fraunhofer.de
Fraunhofer Institute for Physical Measurement Techniques IPM, Freiburg | www.ipm.fraunhofer.de/en